BGA Heat Sink (High Aspect Ratio Ext.) Slant Fin

ATS014014007-MF-3F ATS Part#:


14 X 14 X 7 mm **Description:**


BGA Heat Sink (High Aspect Ratio Ext.) Slant Fin

Component:

Heat Sink Type: Slant Fin

Heat Sink Attachment: N/A





- » Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- » Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option




Images for illustration purposes only.

Thermal Performance

AIR VELOCITY THERMAL RESISTANCE	@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
Unducted Flow (°C/W)	29.2	22.9	19.7	17.6	16.1	15.0	14.0
Ducted Flow (°C/W)	16.7	14.1	12.5	11.3	10.5	9.8	9.3

Product Details

SCHEMATIC IMAGE	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
	14.0 mm	14.0 mm	7.0 mm	14.3 mm	N/A	BLACK-ANODIZED



NOTES:

- Dimension A and B refer to component size
- Dimension C is the heat sink height from the bottom of the base to the top of the fin field.
- Dimension D is fin tip to fin tip.
- Thermal performance data are provided for reference only. Actual performance may vary by application.
- ATS reserves the right to update or change its products without notice to improve the design or performance.
- ATS certifies that this heat sink assembly is RoHS and REACH compliant.
- Contact ATS to learn about custom options available.



*All Images are for illustration purposes only.

